



Schraubenausdreher, zylindrisch

gerade hinterfräste Flanken,
zylindrisch,
selbstschneidend,
nicht materialverdrängend,
für Rechts- **und** Linksgewinde,
US-Alloy-Steel, brüniert




Art.-Nr.	für Schrauben	Vorbohr-Ø mm - Zoll	Vorbohrtiefe mm	● Antrieb Zoll	↔ MAX mm	⚖ g
10650	M 6 - 8	3,0 1/8	5	1/4	38	8
10651	M 8 - 10	4,5 11/64	5	1/4	38	8
10652	M 10 - 12	6,0 15/64	9	5/16	38	13
10653	M 12 - 14	7,0 9/32	9	5/16	38	14
10654	M 14 - 18	9,5 3/8	9	1/2	38	33

10655	M 6 - 18	alle Größen im Satz, 5-teilig			110 x 180	105
-------	----------	-------------------------------	--	--	-----------	-----

Schraubenausdreher, konisch

gerade hinterfräste Flanken,
konische Form:
vorbohren, einschlagen und durch
Linksdrehen Schraubbolzen ausdrehen,
US-Alloy-Steel, brüniert



Art.-Nr.	für Schrauben	Vorbohr-Ø mm - Zoll	Vorbohrtiefe mm	■ Antrieb mm	↔ MAX mm	⚖ g
10561	M 6 - 8	3,0 1/8	10	5,0	65	10
10562	M 8 - 10	4,5 3/16	12	5,0	65	10
10563	M 10 - 12	6,0 15/64	12	6,0	70	16
10564	M 12 - 14	8,0 5/16	12	8,0	75	30
10565	M 14 - 18	9,5 3/8	16	9,0	80	40

10560	M 6 - 18	alle Größen im Satz, 5 teilig			115 x 125	120
-------	----------	-------------------------------	--	--	-----------	-----

